

# 3050MHz VOLTAGE CONTROLLED OSCILLATOR

ACRO-300-3050



Dimensions: 0.91 x 0.91 x 0.22in

## STANDARD SPECIFICATIONS:

	Min	Typ	Max	Units	Cond.
Frequency Range		3050		MHz	1
Tuning Voltage	0		5	V	1
Modulation Sensitivity		5		MHz/V	3
Operates with Vtune = 0V					3
Output Power	5	7	9	dBm	1
Phase Noise					
1KHz Offset		-90		dBc/Hz	2
10KHz Offset		-115		dBc/Hz	3
100KHz Offset		-135		dBc/Hz	2
1MHz Offset		-144		dBc/Hz	2
Pushing			3	MHz/V	3
Pulling (14 db R.L.)			3	MHz	3
Modulation Bandwidth:		N/A		MHz	4
Tuning Port Capacitance				pF	2
Harmonics			-10	dBc	3
Sub-Harmonics	2 <sup>nd</sup>	N/A		dBc	3
	3 <sup>rd</sup>			dBc	3
	4 <sup>th</sup>			dBc	3
Vcc		11		V	5
Icc		24		mA	5
Operating Temperature	-40		+85	C	3
Package		0.91		inch sq.	5

## COND. NOTES:

1. Tested in production
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection

## MARKING:

- 2450
  - ACV2ZY
- (Z for month, Y for year  
ex. D3 for April 2003)

## NOTES:

1. Except for output pins, bottom is solid ground plane
2. All dimensions in mils.
3. All holes are plated through


LABEL ARROW POINTS TO RF OUT

### PINOUT

P3 = RF OUT  
P11 = Vtune  
P15 = Vcc  
ALL OTHER PINS = GND

OPTION T for Tape and Reel

## OUTLINE DRAWING:



Dimensions: inch (mm)