

1190MHz VOLTAGE CONTROLLED OSCILLATOR

ACV2-100-1190



Dimensions: 0.50 x 0.50 x 0.22in

STANDARD SPECIFICATIONS:

	Min	Typ	Max	Units	Cond.
Frequency Range	1190		1610	MHz	1
Tuning Voltage	0.5		8.5	V	1
Modulation Sensitivity		68		MHz/V	3
Operates with Vtune = 0V					3
Output Power	8	10	14	dBm	1
Phase Noise					
1KHz Offset		-74		dBc/Hz	2
10KHz Offset		-99		dBc/Hz	3
100KHz Offset		-119		dBc/Hz	2
1MHz Offset		-139		dBc/Hz	2
Pushing			15	MHz/V	3
Pulling (14 db R.L.)			15	MHz	3
Modulation Bandwidth:	5			MHz	4
Tuning Port Capacitance			100	pF	2
Harmonics			-7	dBc	3
Sub-Harmonics	2 nd	N/A		dBc	3
	3 rd			dBc	3
	4 th			dBc	3
Vcc		10		V	5
Icc		23		mA	5
Operating Temperature	0		+80	C	3
Package		0.50		inch sq.	5

COND. NOTES:

1. Tested in production
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection

MARKING:

- 2450
 - ACV2ZY
- (Z for month, Y for year
ex. D3 for April 2003)

NOTES:

1. Except for output pins, bottom is solid ground plane
2. All dimensions in mils.
3. All holes are plated through


LABEL ARROW POINTS TO RF OUT

PINOUT

P3 = RF OUT
P11 = Vtune
P15 = Vcc
ALL OTHER PINS = GND

OPTION T for Tape and Reel

OUTLINE DRAWING:



ABRACON IS
ISO 9001 / QS 9000
CERTIFIED

rev1.1-9/05



30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com