

SMD ONE PORT 310.00E MHz SAW RESONATOR

ASR310S2

APPLICATION: Remote Control / Wireless Alarms



5 x 3.5 x 1.5mm

STANDARD SPECIFICATIONS:

CHARACTERISTICS		UNIT	MIN.	TYP.	MAX.
Center Frequency Fo		MHz	309.925	310.000	310.075
Tolerance from Fo		KHz		±75	
Insertion Loss		dB	-	1.5	2.2
Quality Factor	Unloaded	-		15,333	
	50Ω loaded			2,000	
Temperature Stability	Turnover Temperature	°C	24	39	54
	Turnover Frequency	KHz		Fc	
	Freq. Temp. Coefficient	ppm/°C ²		0.037	
Frequency Aging		ppm/year		±10	
DC Insulation Resistance		MΩ	1.0		
RF Equivalent RLC Model	Motional Resistance R ₁	Ω		19	29
	Motional Inductance L ₁	μH		118.143	
	Motional Capacitance C ₁	fF		2.2333	
	Shunt Capacitance C ₀	pF	1.8	2.1	2.4
Operating temp.		°C	-40°C to +85°C		
Storage temp.		°C	-40°C to +85°C		
Max. Rating	DC voltage	V	±10		
RF Power Dissipation		dBm	10		


Electrostatic Sensitive Device. Handle with precaution.

MARKING:

- ASR310 ZYX
 (Z for month from A to L;
 Y for year, i.e. 4 for 2004,
 X: Traceability code)

PIN NO.	CONNECTIONS
1	Input/Output
3	Output/Input
2 & 4	Case Ground

TEST CIRCUIT:



NOTES:

- 1) Frequency aging is specified at 65°C or less.
- 2) The center frequency Fc, is the frequency of minimum IL with the resonator in the specified test fixture in a 50Ω test system with VSWR ≤ 1.2.
- 3) Unless otherwise specified, case temperature is 25°C ± 2°C.
- 4) The design model values are for reference only. The capacitance C0 is the measured static capacitance between either pin 1 and ground or pin 2 to ground.

OUTLINE DRAWING:

